

CSW200UL AC HIGH-TRAFFIC COMMERCIAL SWING GATE OPERATOR

For the most demanding high-traffic swing gate environments.



PRODUCT HIGHLIGHT
CONTINUOUS-DUTY,
High-Temperature Motor

RELIABLE

LEGACY ELITE HEAVY-DUTY COMMERCIAL GEAR-DRIVEN TRANSMISSION PROVIDES UNSURPASSED RELIABILITY.

SURGE SUPPRESSION PROVIDES INDUSTRIAL SURGE AND LIGHTNING PROTECTION AGAINST STRIKES UP TO 50 FEET AWAY.

WARRANTY 5 YEARS COMMERCIAL, 7 YEARS RESIDENTIAL.

SMART

myQ® TECHNOLOGY ENABLES YOU TO SECURELY CONTROL AND MONITOR YOUR GATE OPERATOR FROM ANYWHERE.*

WIRELESS DUAL-GATE COMMUNICATION SYNCHRONIZES GATE OPENING/CLOSING AND ELIMINATES EXPENSIVE DRIVEWAY TRENCHING COSTS.

SYNCHRONIZED CLOSE SIMULTANEOUSLY CLOSES GATES.

SAFE AND SECURE

SECURITY+ 2.0® SAFEGUARDS FACILITY ACCESS WITH ROLLING CODE TECHNOLOGY, OPENING FOR REGISTERED DEVICES ONLY.

EMERGENCY DISCONNECT: SIMPLE-TO-USE RELEASE HANDLE ALLOWS GATE TO BE OPERATED MANUALLY AND MAINTAIN LIMIT POSITION ONCE REENGAGED.

INHERENT REVERSING SENSOR DETECTS OBSTRUCTIONS AND REVERSES GATE WHEN CLOSING OR STOPS/REVERSES THE GATE WHEN OPENING.

QUICK CLOSE AND ANTI-TAILGATE QUICKLY SECURE PROPERTY, PREVENTING UNAUTHORIZED ACCESS.

UL® LISTED GATE OPERATORS WITH MONITORED SAFETY ENTRAPMENT PROTECTION DEVICES.

*Cellular data or Wi-Fi® connection required. Test equipment regularly and follow safety instructions.

INCLUDED ACCESSORIES:

MONITORED RETRO-REFLECTIVE PHOTO EYE

Enhanced retro-reflective photo eye now with heater and wider beam, engineered to stay aligned; max. range: 50 ft.



LMRRLU

SAFETY ADD-ONS:

MONITORED THROUGH-BEAM PHOTO EYES

Enhanced through-beam now with wider beam and heater for high performance in most environments; max. range: 90 ft.



LMTBUL

MONITORED WIRELESS EDGE KIT

Low-energy Bluetooth® connection between a LiftMaster Monitored Resistive Edge and the gate operator; max. range: 130 ft.**



LMWEKITU

MONITORED SAFETY ENTRAPMENT EDGES

Full line of Small, Large and Wraparound Profile Edges that sense obstructions.



EDGES

TOTAL SOLUTION ACCESSORIES:

CONNECTED ACCESS PORTAL, HIGH CAPACITY

Cloud-based access control for residential communities.



CAPXL

WIRELESS COMMERCIAL KEYPAD

Provides constant pressure override to control gate operator if safety devices fault yet are free of obstructions. Hold Open/Party Pass enabled with gate operator firmware 4.2 or higher.



KPW250

PLUG-IN LOOP DETECTOR

Prevents the gate from closing on a vehicle in the path; power efficient for maximum cycles on Battery Backup.



LOOPDETLM

**Wireless kit for up to 4 transmitters and 2 resistive edges per transmitter.

MASTERFUL ENGINEERING.

MECHANICS

- **Continuous-Duty Motor** Rated for High-Cycle, High-Temperature Applications (Available in 1/2 and 1 HP)
- **Wormgear Reduction:** 2 Commercial Oil-Bath Gearboxes Providing 900:1 Wormgear Reduction

POWER


- **115V Single-Phase**
- **Accessory Power:** 24VDC 500mA Output
- **Optional Kit (3PHCONV)** to Convert an Input Voltage of 208/240/460/575VAC to an Output Voltage of 115VAC

COMMERCIAL-GRADE DESIGN

- **Chassis:** Constructed with 1/4 in. black powder coated steel for rust prevention
- **Cover:** High-Density, 2-Piece UV-Resistant Polyethylene Cover (1/2 HP CSW200501UL)
- **UL® Usage Classification:** I, II, III and IV
- **Operator Weight:** 175 lbs.


1/2 HP CSW200501UL

CAPACITIES



1 HP CSW200101UL

CAPACITIES



TEMPERATURE SPECIFICATIONS



- WITHOUT HEATER**
-4°F (-20°C) to 140°F (60°C)
- WITH OPTIONAL HEATER (HTRNB)**
-40°F (-40°C) to 140°F (60°C)



GATE TRAVEL SPEED
Opens 90° in 13–15 Seconds

STANDARD FEATURES.

PRE-MOTION WARNING ALARM

- Activates On-Board Alarm 3 Seconds Prior to Gate Motion

BI-PART DELAY

- Monitors and Adjusts Speed and Position of Each Wing to Ensure Primary Gate Closes Last

MECHANICAL LIMIT SYSTEM

- Maintains Accurate Gate Position Throughout Gate Travel, Even After Using Manual Disconnect

MONITORED SAFETY INPUTS

- 3 Main Board, 3 Expansion Board

SECURITY+ 2.0® ON-BOARD RADIO RECEIVER

- Up to 50 Remote Controls (Unlimited with 811LMX/813LMX)

LED DIAGNOSTIC DISPLAY

- Simplifies Installation and Troubleshooting

PROGRAMMABLE AUXILIARY RELAYS

- Make Adding Additional Features Easy

SUPPORT.



For Support Tools and Training Videos, Visit LiftMasterTraining.com

For More Information on Gate Operators, Visit LiftMaster.com/UL325Gates

To Find the Right Perimeter Access Solution for You, Visit LiftMaster.com/Solution-Generator



Sales Support: 800.282.6225
Technical Support Center: 800.528.2806
To Order: 800.323.2276

