TELEPHONE ENTRY / ACCESS CONTROL SYSTEM EL25

SECTION 28 13 00

-

KEY FEATURES

UNIT INTERFACE CAPABILITIES PIN/transmitter/voice

STAND ALONE Yes

SCHEDULING CAPABILITIES Yes

RADIO RECEIVER Optional

SPECIFICATIONS

DATA CONNECTIVITY Dial-up modem/direct connect/keypad

VOICE COMMUNICATION POTS/filtered DSL

CALLING CONNECTIVITY POTS

POWER SUPPLY 120VAC to 16VDC transformer (included in carton)

PROGRAMMING (DATABASE MANAGEMENT)

Cloud backup/keypad

REMOTE PROGRAMMING (DATABASE MANAGEMENT) Yes

SOFTWARE VERSA XS 4.0

WIEGAND INPUT DATA FORMAT 26 and 30 Bit LOCAL USER CAPACITY 2000

EVENT HISTORY 8000

MAX NUMBER OF GATES/DOORS OF CONTROL (EACH) 4

WIEGAND INPUT 4

 RELAY OUTPUT
 2 (1 primary, 1 auxilliary)

 MOUNTING OPTIONS
 Surface/flush/gooseneck

 OPERATING TEMPERATURE
 -4°F to 149°F (-20°C to 65°C)

CAMERA READY

ANTI-TAMPER ALARM

WARRANTY

Yes

2 years

CONSTRUCTION

ENCLOSURE MATERIAL Zinc-alloy



TELEPHONE ENTRY / ACCESS CONTROL SYSTEM EL25

SECTION 28 13 00





