

Smooth Running, Powerful Performance

Performance

- P3[™] Motors are reliable, durable and powerful designed specifically for your needs.
- 1/2 HP AC motor with industrial-strength screw drive provides steady performance and lifting power.
- Motor Vibration Isolation System (MVIS®) provides super quiet, smooth operation year after year.
- · 200-watt lighting with adjustable light time delay for more energy-efficient use
- One-piece steel rail design means less friction so no binding or lubrication is needed even in the most extreme temperatures.
- Lifetime motor warranty and 1-year parts warranty.

Safety and Security

- **Security+**® safeguards your household with every click a new code is sent to the garage door opener so that the door opens only for you.
- PosiLock® locks down your door by electronically monitoring against a forced opening.
- The Protector System® has safety sensors that project a light beam across
 the garage door opening, automatically reversing the door if anything
 interrupts the beam.

Included Accessories:



3-Button Remote Control (373LM)

Allows you to control up to three garage door openers or gate operators.



Multi-Function Control Panel (78LM)

Enables you to turn garage door opener lights on and off from inside the garage.

Optional Accessories:



Wireless Keyless Entry (877MAX)

Open your garage door without using a remote control and close it with just the push of a button. You can also program a temporary entry code for friends and service people.



3-Button Mini Remote Control (890MAX)

Allows you to operate up to three garage door openers, gate operators or MyQ[®] Light Accessories. Fits on keychain, in a pocket or purse.



MyQ Control Panel (888LM)

Allows any LiftMaster Garage
Door Opener manufactured since
1998 to be controlled by your
smartphone, tablet or computer
(when paired with the Internet
Gateway) – provides the upgrade
needed to utilize Security+ 2.0
and MyQ Technology.



Ceiling Mount (195LM)

Give your garage the style it's been missing by hiding the wires and cords with this sleek ceiling mount. Works in most standard garages.



SPEC SHEET STANDARD SPECIFICATIONS

DIMENSIONS

Installed Length: 128" Maximum Door Opening: 7' 6" 1/2"* Headroom Clearance Required: 2.3"

*Up to 8' 6" with optional rail

CARTONS

Number of Cartons: 2

Carton 1: Dimensions and Contents:

- 20" x 8 1/8" x 20"
- Multi-Function Control Panel
- 373LM Remote Control
- Garage Door Opener Head
- The Protector System®

Carton 2: Dimensions and Contents:

- 114" x 3" x 3"
- Assembled Solid-Steel Screw Rail

SECURITY+® RADIO CONTROLS

Coding System: Smart Receiver Code Button and Indicator Light

Operating Range: 150' (approximately) Operating Temperature: -40°F to 150°F Battery (remote control): 3-Volt Lithium Frequency: 315MHz

373LM 3-Button Remote Control Security+ Anti-Burglary Coding

CONVENIENCE / SAFETY

The Protector System Emergency/Quick Release Automatic Trolley Reconnect Ventilation/Pet Opening Down Safety Reverse Up Safety Stop Door Open/Beam Broken/Lights On

PosiLock® secure lock system

ELECTRICAL SPECIFICATIONS

POWER

Voltage: 120V AC, 60Hz Current Rating: 4.5 UL Listings: Yes

Length of Line Cord: 4' (3-prong)

LOGIC TYPE

Solid State Microcontroller with Built-in Surge Suppressor

LIGHTING

Number of Bulbs: 2 Maximum Wattage: 100 x 2 Length of Light Delay: Adjustable Type of Light Delay: Solid-State

MECHANICAL SPECIFICATIONS

MOTOR

Horsepower: 1/2 RPM: 1,625 Thermal Protection: Automatic Lubrication: Permanent

DRIVE MECHANISM

Drive Means: Screw Reduction Means: Belt

Door Linkage: Adjustable Door Arm

ADJUSTMENTS

Force: Internal Up and Down Limit: Internal

TRAVEL RATE

Approximately 7.5" per second

SHIPPING WEIGHTS

Head: 22 lbs. Rail: Screw-23 lbs.

MATERIALS

Chassis and Chassis Cover: Steel

Rail: Steel Trolley: Steel

WARRANTY

Lifetime Motor Warranty 1 Year Parts and Accessories Warranty

HOMELINK® Compatible (version 4.0 or higher) *May require an external adapter depending on the model and year of your vehicle. Visit homelink.com for additional information.

