# DC BATTERY BACKUP CHAIN DRIV WI-FI® GARAGE DOOR OPENER

Ultra-powerful performance for wind-load and heavy doors.



DC INTEGRATED BATTERY BACKUP MOTOR CHAIN DRIVE SYSTEM PROVIDES MAXIMUM POWER FOR PROPERLY BALANCED HEAVY DOORS UP TO 750 LBS.

I-BEAM RAIL SYSTEM AND REINFORCED CHASSIS MAXIMIZE SUPPORT.

WARRANTY LIFETIME MOTOR, 5-YEAR PARTS AND 1-YEAR ACCESSORIES.

# SECURE

AUTOMATIC GARAGE DOOR LOCK CAPABLE: DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY myQ®.

TIMER-TO-CLOSE CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

# **SMART**

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

FREE myQ MOBILE APP SO USERS KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA FMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

#### **INCLUDED ACCESSORIES:**

#### **SMART CONTROL PANEL®**

LCD display enables simple programming and adjustment of settings.



880LMW

#### **3-BUTTON REMOTE CONTROL**

Operates up to 3 openers or myQ Light Accessories.



893MAX

#### INTEGRATED BATTERY BACKUP

Powers up the opener when the power's out



#### **POWERFUL ADD-ONS:**

#### **AUTOMATIC GARAGE** DOOR LOCK CAPABLE

Deadbolts the garage door automatically every time it closes.





825LN

#### REMOTE LIGHT CONTROL

MINI UNIVERSAL

Plug in any lamp to this device to control it with a smartphone or garage remote.





REMOTE CONTROL Compact and portable to provide quick, easy garage access.



#### WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



The State of California has not endorsed these or any other garage door openers.

# MASTERFUL ENGINEERING.

DC BATTERY BACKUP CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

#### MOTOR -



#### -12 VDC

- -53 RPM
- Permanent Lubrication
- Lift heavy doors and carraige house doors up to 750 LBS.

#### POWER -



- -60 Hz Voltage
- -3.5A Current Rating
- -III Listed
- -6' Power Cord (3-Prong)

# 4 LiftMaster

#### MECHANICS



- Steel Chassis, I-Beam and Trolley
- Full Chain Drive Mechanism (16:1 Gear Reduction and Adjustable Door Arm)
- Auto-Force Adjustment for Changing Weather and Environmental Conditions
- Electronic Limits for Easy Setup
- Sprocket: 10-Tooth
- DC Wi-Fi Logic Board with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWFLK)
- -2 Lock Terminals Allow up to 2 Locks to Be Connected (Sold Separately)

#### DIMENSIONS

| Rail Options     | 7'   | 8'   | 10'   | 12'   | 14'   |
|------------------|------|------|-------|-------|-------|
| Installed Length | 125" | 140" | 164"  | 189"  | 213"  |
| Max. Opening     | 7'6" | 8'6" | 10'6" | 12'6" | 13'6" |

Headroom Clearance Required: 2"

5 11 **SPEED** 

Per second for door to move upward

Per second for door to move

# downward

611

# STANDARD SPECS.

#### SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200 

Operating Temperature: -40°F to 150°F

- 3-Button Remote Control (893MAX)
- -Remote Control: 310, 315 and 390 MHz Tri-Band\*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding
- \*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

#### **ENCRYPTED CONTROLS**

Smart Control Panel® (880LMW)

- Timer-to-Close
- Program Remote Controls, Keypads and myQ Accessories
- Maintenance Alert System
- Easy Wi-Fi Setup

#### myQ® RADIO



- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

#### **HOMELINK® COMPATIBLE** (VERSION 4.0 OR HIGHER\*)

\*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

#### LIGHTING





- Max. 2 100-Watt Lightbulbs
- Adjustable Time
- Solid-State Delay
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

# SHIPPING.

SHIPPING WEIGHT (in lbs.)







SUPPORT

#### CARTONS (3)

CARTON 1: 19.81" x 11.94" x 11.19"

- Garage Door Opener Head (8580WLB)
- -Battery (485LM)
- Smart Control Panel (880LMW)
- -3-Button Remote Control (893MAX)
- -The Protector System® Safety Reversing Sensors
- Safety Sensor Extension Brackets

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain I-Beam

CARTON 3: 11.19" x 2.69" x 10.56"

- Support Bracket (041C5069)

#### SAFETY AND SECURITY.



- Alert-2-Close/Unattended Close Operation<sup>†</sup>
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening

- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 myQ Devices

† Note: to reduce the risk of injury to persons, only use Alert-2-Close/Unattended Close Operation features when installed with a sectional door.



© 2019 LiftMaster All Rights Reserved 300 Windsor Drive, Oak Brook, IL 60523

Apple is a trademark of Apple Inc., registered in the U.S. and other countries. HomeKit is a trademark of Apple Inc. UL and the UL logo are trademarks of UL LLC @ 2018 All Rights Reserved Wi-Fi® is a registered trademark of Wi-Fi Alliance

LMGDENPG8580WLB 09/19